

REV 1
9-7-23

MODEL NUMBER	VALVE SIZE	END CONNECTIONS
BBL9408S	1" [DN 25]	SIL BRAZED
BBL9408T	1" [DN 25]	1" NPTF THD
BBM9408S	1" [DN 25]	SIL BRAZED
BBM9408T	1" [DN 25]	1" NPTF THD
BBS9408S	1" [DN 25]	SIL BRAZED
BBS9408T	1" [DN 25]	1" NPTF THD

PREFIX	DIM A OPEN	DIM A CLOSED
BBL	14.6 [370]	14.1 [358]
BBM	10.6 [269]	10.1 [257]
BBS	6.7 [170]	6.2 [157]

BBx9408x
BRONZE GLOBE VALVE
W/ SIL BRAZED & THREAD ENDS

TEMPERATURE RANGE: -325°F TO +150°F (-198°C TO +66°C)
PRESSURE RANGE: 720 PSIG (50 BARG)
OXYGEN CLEAN PER CGA 4.1

ITEM	QTY	DESCRIPTION	MATERIAL
1	1	TOP WORKS/UPPSER ASSY	
1.1	1	GASKET	PTFE- VIRGIN GRADE 25% GLASS FILLED
1.2	1	SEAT DISC ASSY	
1.2.1	1	HOLDER, SEAT DISC	BRASS-360 FC ASTM B16 (UNS C36000)
1.2.2	1	RETAINER, SEAT	BRASS-360 FC ASTM B16 (UNS C36000)
1.2.3	1	DISC, SEAT	PCTFE-ASTM D1430 CL 1 GRD 3
1.3	1	NUT, STEM	BRONZE-932 LEAD TIN ASTM B505 (UNS C93200)
1.4	1	PACKING, ADAPTER	BRASS-360 FC ASTM B16 (UNS C36000)
1.5	5	PACKING, BONNET	PTFE- VIRGIN GRADE TFE-FLUOROCARBON
1.6	4	PACKING, SEPARATOR	BRASS-360 FC ASTM B16 (UNS C36000)
1.7	1	FOLLOWER, GLAND	BRASS-360 FC ASTM B16 (UNS C36000)
1.8	1	BEARING, BONNET	PTFE- VIRGIN GRADE
1.9	1	WASHER, LIVE-LOADING	BRASS-360 FC ASTM B16 (UNS C36000)
1.10	1	NUT, BONNET	STAINLESS STEEL-303 ASTM A582 (UNS S30300)
1.11	4	SCREW, 3/8-16 X 1.000 LG	STAINLESS STEEL-304 ASTM A182 (UNS S30400)
1.12	1	NUT, HEX	300 SER STAINLESS STEEL
1.13	1	WASHER	STAINLESS STEEL-304 (UNS S30400)
1.14	1	RING, RETAINING	STAINLESS STEEL-302 ASTM A313 (UNS S30200)
1.15	1	STEM	STAINLESS STEEL-304 ASTM A276 (UNS S30400)
1.16	1	HANDWHEEL, CAST	ALUMINUM-380 ASTM B85 (UNS A03800)
1.17	2	WASHER, SPRING	301 STAINLESS STEEL
1.18	1	MACH, BONNET & TUBE	STAINLESS STEEL-304 ASTM A182 (UNS S30400)
2	1	BODY	BRONZE-922 ASTM B61 (UNS C92200)

